



ADVANTAGES

ReproSound polyethylene foam underlayment offers protection for all brands of applicable flooring. This padding provides a cost efficient source of underlayment for the installation of wood floors. Our foam underlayment products utilize the latest technology to assure protection while meeting specifications.

- Self Sealing film lip and adhesive liner tape added for easier installation
- 100% reprocessed foam resin.
- Offers protection and comfort for underneath all brands of applicable flooring.
- Softens and insulates noise
- Economical, cost efficient
- Provides water and moisture protection

PRODUCT SPECIFICATIONS

Foam Thickness	.120
Compression Set	ASTM D3575-93 - 22.5%
R Factor	3 per inch
Impact Insulation Class	ASTM E492-09 - IIC 59
Delta Sound Test Results	ASTM E2179-03 - Δ IIC 22
Water Vapor Transmission Rate	g/sqm/24 hrs - ASTM D1653 - .40



INSTALLATION INSTRUCTIONS

- Always read the flooring manufacturers recommendations and instructions before installing the underlayment.
- Before rolling out the underlayment, be sure to sweep, vacuum, and remove all debris on the substructure.
- Fill in any significant holes, gaps or breaks that may exist on the substructure.
- Roll out the underlayment over the substructure surface.
- Install underlayment with self sealing tape by simply connecting the extended film lip to the opposite side of the next roll by peeling the liner off the tape and attaching the adhesive to the film lip.
- Always be sure to connect the rolls together evenly so that the foam is not overlapping each other and there are no wide gaps between the foam.