

SoundOFFTM200

Underlayment Foam **SELF SEAL**



A D V A N T A G E S

SoundOff Premium Grade underlayment offers protection for all brands of applicable flooring. This padding provides a cost efficient source of underlayment for the installation of wood floors. Our foam underlayment products utilize the latest technology to assure protection while meeting specifications.

- Self Sealing film lip and adhesive liner tape added for easier installation
- Offers protection and comfort for underneath all brands of applicable flooring.
- Softens and insulates noise
- Economical, cost efficient
- Superior water and moisture protection

P R O D U C T S P E C I F I C A T I O N S

| | |
|-------------------------------|--------------------------------------------------|
| Foam Density | 5.5# density |
| Foam Thickness | .115 |
| Compression Set | ASTM D3575-93 - 13.5% |
| R Factor | 3 per inch |
| Impact Insulation Class | ASTM E492-09 - IIC 60 |
| Delta Sound Test Results | ASTM E2179-03 - ΔIIC 22 |
| Water Vapor Transmission Rate | g/100²/day F1249 — .066 |



I N S T A L L A T I O N I N S T R U C T I O N S

- Before rolling out underlayment, be sure to sweep, vacuum, and remove all debris on the substructure.
- Fill in any significant holes, gaps or breaks that may exist on substructure.
- Roll out underlayment over the substructure.
- Always follow the flooring manufacturers instructions when installing underlayment in areas with a high concentration of water, moisture, and vapor transmissions.
- Install underlayment with self sealing film lip and adhesive tape by simply connecting the extended film lip to the opposite side of the next roll by peeling the liner off the tape and attaching the adhesive to the film lip.
- Always be sure to connect the rolls together evenly so that the foam is not overlapping each other and there are no wide gaps between the foam before splicing.